

SUBMITTAL DATA - WALL-MOUNTED

MWMA009S4-3P

MULTI-ZONE MINI-SPLIT HEAT PUMP

Engineer:
Architect:
Date:
For: Reference Reproval Review Construction

FEATURES

Job:
Location:
Schedule No.:
System Designation:

- Pre Heat Function
- Multi-Refrigerant Outlet
- Auto RestartThree Speed Fan
- Flare Connections
- Refrigerant R-410A
- · LED Readout Panel
- · Wireless Remote Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

Product registration required.			
SPECIFICATIONS			
PERFORMANCE			
Cooling Capacity ¹ (Btu/h)		9,000	
Heating Capacity ¹ (Btu/h)		10,000	
Airflow (CFM)	High	340	
	Medium	260	
	Low	205	
External Static Pressure (in. w.g.)			
Sound Pressure (dBA)	High	43.3	
	Medium	36.2	
	Low	29.1	
ELECTRICAL DATA			
Power Supply (V/Hz/Φ)		208-230/60/1	
Power Supply (V/Hz/Φ) Rated load amps (RLA)		208-230/60/1 0.20	
Rated load amps (RLA)		0.20	
Rated load amps (RLA) Power Output (W)	Height	0.20	
Rated load amps (RLA) Power Output (W) DIMENSIONS	Height Width	0.20 20	
Rated load amps (RLA) Power Output (W) DIMENSIONS	•	0.20 20 11	
Rated load amps (RLA) Power Output (W) DIMENSIONS	Width	0.20 20 11 32-7/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in)	Width	0.20 20 11 32-7/8 7-7/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in)	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in)	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4 3/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection	Width Depth	0.20 20 11 32-7/8 7-7/8 1/4 3/8	



OPTIONAL ACCESSORIES Non-Programmable Controller (M0STAT61Q-1): Wireless Remote Controller (M0STAT60Q-1): 1+ Programmable Controller (M0STAT64Q-1): Mini-Split IDU Controls Wiring Harness (19P86)* *Required for BACnet & Lennox VRF Manager (LVM)

NOTES

1. Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor











SUBMITTAL DATA - WALL-MOUNTED

MWMA009S4-**3**P

MULTI-ZONE MINI-SPLIT HEAT PUMP

DIMENSIONAL DRAWINGS - INCHES (MM)

