

SUBMITTAL DATA - WALL-MOUNTED

MWMA024S4-2P

MULTI-ZONE MINI-SPLIT HEAT PUMP

| Engineer: |
|---|
| Architect: |
| Date: |
| For: Reference Approval Review Construction |

FEATURES

Job:
Location:
Schedule No.:
System Designation:

- Pre Heat Function
- Multi-Refrigerant Outlet
- Auto Restart
 Three Speed Fan
- Flare Connections
- Refrigerant R-410A
- · LED Readout Panel
- · Wireless Remote Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

| Product registration required. | | |
|--|-----------------|--|
| SPECIFICATIONS | | |
| PERFORMANCE | | |
| Cooling Capacity ¹ (Btu/h) | | 23,000 |
| Heating Capacity ¹ (Btu/h) | | 25,000 |
| Airflow (CFM) | High | 750 |
| | Medium | 690 |
| | Low | 565 |
| External Static Pressure (in. w.g.) | | |
| Sound Pressure (dBA) | High | 50.0 |
| | Medium | 44.7 |
| | Low | 39.4 |
| ELECTRICAL DATA | | |
| | | |
| Power Supply (V/Hz/Φ) | | 208-230/60/1 |
| Power Supply (V/Hz/Φ) Rated load amps (RLA) | | 208-230/60/1 0.50 |
| | | |
| Rated load amps (RLA) | | 0.50 |
| Rated load amps (RLA) Power Output (W) | Height | 0.50 |
| Rated load amps (RLA) Power Output (W) DIMENSIONS | Height Width | 0.50 60 |
| Rated load amps (RLA) Power Output (W) DIMENSIONS | • | 0.50 60 13-1/2 |
| Rated load amps (RLA) Power Output (W) DIMENSIONS | Width | 0.50 60 13-1/2 46-3/4 |
| Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) | Width | 0.50 60 13-1/2 46-3/4 10-1/4 |
| Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) | Width Depth | 0.50 60 13-1/2 46-3/4 10-1/4 3/8 |
| Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) | Width Depth | 0.50 60 13-1/2 46-3/4 10-1/4 3/8 5/8 |
| Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection | Width Depth | 0.50 60 13-1/2 46-3/4 10-1/4 3/8 5/8 |



OPTIONAL ACCESSORIES Non-Programmable Controller (M0STAT61Q-1): Wireless Remote Controller (M0STAT60Q-1): 1+ Programmable Controller (M0STAT64Q-1): Mini-Split IDU Controls Wiring Harness (19P86)* *Required for BACnet & Lennox VRF Manager (LVM)

NOTES

1. Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor











SUBMITTAL DATA - WALL-MOUNTED

MULTI-ZONE MINI-SPLIT HEAT PUMP

MWMA024S4-**2**P

DIMENSIONAL DRAWINGS - INCHES (MM)

